#### **Basic Use Case Template**

Alistair Cockburn email: arc@acm.org home page: http://alistair.cockburn.us

Document: TR.96.03a This Version Date: October 26, 1998 Version: 2 Previous Version Date: April 26, 1996

Per popular request, I am putting forward a basic template for use cases matching the document "Structuring Use Cases with Goals", HaT.TR.95.1 (available at the same address and web site), and the course / tutorial of a similar name. This document is copyrighted by Humans and Technology as HaT technical report TR 96.03a, also found at http://alistair.cockburn.us. You have permission to copy and distribute the documents as long as you reference the source of the originals. You may use the templates in courses and presentations with proper reference. You may use and vary the template on your projects without reference. Do note that the template may evolve over time according to your feedback. *Additions to the text may appear in italics, like this (added, v.2)*.

The template has the sections: name (which is the goal), goal in context, scope, level, trigger, pre- and postconditions, main course, extensions, sub-variations, and other characteristic data for the use case. You may easily graft more information on to the end, or omit information. To help you decide when to omit information, I include a section on Using, Staging, Tailoring the Template. The base template is given twice, once in simple word-processing format and then again in table format so you can choose the one that best suits your tool set. Personally, I find that people work best with the simple text format. You will find that the collection of use cases is easier to work with in something like Lotus Notes than in a word processor.

In this version of the template, I write Sub-Variation as an attempt to make it more distinct from Extensions. Refer to the original paper.

This document has the following parts:

- Template in plain text
- Template in table form
- Example in plain text
- Example in table form
- Using, Staging, Tailoring the Template

The Word binary of this document may be available on the web site.

Use Case: <number> <the name should be the goal as a short active verb phrase>

## -----

## CHARACTERISTIC INFORMATION

<u>Goal in Context:</u> <a longer statement of the goal, if needed> <u>Scope:</u> <what system is being considered black-box under design>

Level: <one of: Summary, Primary task, Subfunction>

Preconditions: < what we expect is already the state of the world>

Success End Condition: < the state of the world upon successful completion>

Failed End Condition: < the state of the world if goal abandoned>

Primary Actor: <a role name for the primary actor, or description>

Trigger: <the action upon the system that starts the use case, may be time event>

## 

MAIN SUCCESS SCENARIO

<put here the steps of the scenario from trigger to goal delivery, and any cleanup after>
<step #> <action description>

# EXTENSIONS

cut here there extensions, one at a time, each refering to the step of the main scenario>condition> : <action or sub.use case>

<step altered < condition > . <action of sub-use case>

<step altered> <condition> : <action or sub.use case>

## SUB-VARIATIONS

## RELATED INFORMATION (optional)

<u>Priority:</u> <how critical to your system / organization>

Performance Target: <the amount of time this use case should take>

Frequency: < how often it is expected to happen>

Superordinate Use Case: <optional, name of use case that includes this one> Subordinate Use Cases: <optional, depending on tools, links to sub.use cases>

Channel to primary actor: <e.g. interactive, static files, database>

Secondary Actors: <list of other systems needed to accomplish use case>

<u>Channel to Secondary Actors:</u> <e.g. interactive, static, file, database, timeout>

\_\_\_\_\_

OPEN ISSUES (optional)

list of issues about this use cases awaiting decisions>

## SCHEDULE

<u>Due Date:</u> <date or release of deployment>

...any other schedule / staffing information you need...

Table format:

	r		
USE CASE #	< the name is the goal as a short active verb phrase>		
Goal in Context	<a longer="" statement<="" th=""></a>		
	of the goal in context		
	if needed>		
Scope & Level	<what being="" black="" box="" considered="" design="" is="" system="" under=""></what>		
-	<one :="" of="" primary="" subfunction="" summary,="" task,=""></one>		
Preconditions	<what already="" expect="" is="" of="" state="" the="" we="" world=""></what>		
Success End	<the completion="" of="" state="" successful="" the="" upon="" world=""></the>		
Condition			
Failed End Con-	<the abandoned="" goal="" if="" of="" state="" the="" world=""></the>		
dition			
Primary,	<a actor="" description="" for="" name="" or="" primary="" role="" the="">.</a>		
Secondary Ac-	<other accomplish="" case="" relied="" systems="" to="" upon="" use=""></other>		
tors			
Trigger	<the action="" case="" starts="" system="" that="" the="" upon="" use=""></the>		
DESCRIPTION	Step	Action	
	1	<pre><put here="" of="" pre="" scenario<="" steps="" the=""></put></pre>	
		from trigger to goal delivery, and any cleanup afte>	
	2	<>	
	3		
EXTENSIONS	Step	Branching Action	
	1a	<condition branching="" causing=""> :</condition>	
		<action case="" name="" of="" or="" sub.use=""></action>	
SUB-		Branching Action	
VARIATIONS			
	1	<li>st of variation s&gt;</li>	

RELATED	<use case="" name=""></use>		
INFORMATION			
Priority:	<how critical="" organization="" system="" to="" your=""></how>		
Performance	<the amount="" case="" of="" should="" take="" this="" time="" use=""></the>		
Frequency	<how expected="" happen="" is="" it="" often="" to=""></how>		
Channels to actors	<e.g. database,="" files,="" interactive,="" static="" timeouts=""></e.g.>		
<b>OPEN ISSUES</b>	<li>st of issues</li>		
	awaiting decision		
	affecting this use case >		
Due Date	<date needed="" or="" release=""></date>		
any other	<as needed=""></as>		
management			
information			
Superordinates	<pre><optional, case(s)="" includes="" name="" of="" one="" that="" this="" use=""></optional,></pre>		
Subordinates	<optional, depending="" on="" th="" tools,<=""></optional,>		
	links to sub.use cases>		

Sample:

Use Case: 5 Buy Goods

-----

### CHARACTERISTIC INFORMATION

<u>Goal in Context:</u> Buyer issues request directly to our company, expects goods shipped and to be billed.

Scope: Company

Level: Summary

Preconditions: We know Buyer, their address, etc.

Success End Condition: Buyer has goods, we have money for the goods.

Failed End Condition: We have not sent the goods, Buyer has not spent the money.

<u>Primary Actor:</u> Buyer, any agent (or computer) acting for the customer

Trigger: purchase request comes in.

#### MAIN SUCCESS SCENARIO

1. Buyer calls in with a purchase request.

2. Company captures buyer's name, address, requested goods, etc.

3. Company gives buyer information on goods, prices, delivery dates, etc.

4. Buyer signs for order.

5. Company creates order, ships order to buyer.

6. Company ships invoice to buyer.

7. Buyers pays invoice.

-----

EXTENSIONS

3a. Company is out of one of the ordered items:

3a1. Renegotiate order.

4a. Buyer pays directly with credit card:

4a1. Take payment by credit card (use case 44)

7a. Buyer returns goods:

7a. Handle returned goods (use case 105)

SUB-VARIATIONS

1. Buyer may use

phone in,

fax in,

use web order form,

electronic interchange

7. Buyer may pay by

cash or money order check credit card

-----

RELATED INFORMATION <u>Priority:</u> top <u>Performance Target:</u> 5 minutes for order, 45 days until paid <u>Frequency:</u> 200/day <u>Suberordinate Use Case:</u> Manage customer relationship (use case 2) <u>Subordinate Use Cases:</u> Create order (use case 15) Take payment by credit card (use case 44)

Handle returned goods (use case 105)

<u>Channel to primary actor:</u> may be phone, file or interactice <u>Secondary Actors:</u> credit card company, bank, shipping service <u>Channels to Secondary Actors:</u>

OPEN ISSUES What happens if we have part of the order? What happens if credit card is stolen?

SCHEDULE <u>Due Date:</u> release 1.0 Sample in table format:

	D C	- 1-	
USE CASE 5	Buy G		
Goal in Context	Buyer issues request directly to our company, expects goods shipped and to be billed.		
Scope & Level	Company, Summary		
Preconditions	We know Buyer, their address, etc.		
Success End	Buyer has goods, we have money for the goods.		
Condition			
Failed End Con-	We have not sent the goods, Buyer has not spent the money.		
dition			
Primary,	Buyer, any agent (or computer) acting for the customer.		
Secondary Ac-	Credit card company, bank, shipping service		
tors			
Trigger	purcha	purchase request comes in.	
DESCRIPTION	Step	Action	
	1	Buyer calls in with a purchase request	
	2	Company captures buyer's name, address, requested	
		goods, etc.	
	3	Company gives buyer information on goods, prices, deliv-	
		ery dates, etc.	
	4	Buyer signs for order.	
	5	Company creates order, ships order to buyer.	
	6	Company ships invoice to buyer.	
	7	Buyers pays invoice.	
EXTENSIONS	Step	Branching Action	
	3a -	Company is out of one of the ordered items:	
		3a1. Renegotiate order.	
	4a	Buyer pays directly with credit card:	
		4a1. Take payment by credit card (use case 44)	
	7a	Buyer returns goods:	
		7a. Handle returned goods (use case 105)	
SUB- VARIATIONS		Branching Action	
	1	Buyer may use	
		phone in,	
		fax in,	
		use web order form,	
		electronic interchange	
	7	Buyer may pay by	
		cash or money order	
		check	
		credit card	

RELATED	5. Buy Goods		
INFORMATION			
Priority:	top		
Performance	5 minutes for order, 45 days until paid		
Frequency	200/day		
Channel to actors	not yet determined		
<b>OPEN ISSUES</b>	What if we have part of the order?		
	What is credit card is stolen?		
Due Date	release 1.0		
any other			
management			
information			
Superordinates	Manage customer relationship (use case 2)		
Subordinates	Create order (use case 15)		
	Take payment by credit card (use case 44)		

## Using, Staging, Tailoring the Template

My (and others') experience is that at early stages of the project the template is too long and *too complete* to fill out all at one time - at the beginning of the project, it is appropriate to work with less information (see the chapter, "Managing Precision, Accuracy and Scale" in my book, <u>Surviving Object-Oriented Projects</u>). Therefore...

1. Learn to fill in all the fields of the template in several passes, at several moments in the project's requirements gathering and project setup work. Here is a sample sequence. First, fill in just these fields, for all the use cases you need to consider at this time:

Use Case: <number> <the name should be the goal as a short active verb phrase> <u>Goal in Context:</u> <a longer statement of the goal, if needed> <u>Scope:</u> <what system is being considered black-box under design> <u>Level:</u> <one of: Summary, Primary task, Subfunction> <u>Primary Actor:</u> <a role name for the primary actor, or description> <u>Priority:</u> <how critical to your system / organization> <u>Frequency:</u> <how often it is expected to happen>

2. Stare at what you have so far. Think. Examine. Can you merge or remove some of them? Can you partition them into ones that should be developed together, or written later? For the ones you determine to pursue now, fill in the following fields:

<u>*Trigger:</u> < the action upon the system that starts the use case, may be time event > MAIN SUCCESS SCENARIO*</u>

3. Now you have enough information to check your project's scope and look for surprises. Before you are done describing the system's functioning, you have to fill out:

EXTENSIONS SUB-VARIATIONS <u>Superordinate Use Case:</u> <optional, name of use case that includes this one> <u>Subordinate Use Cases:</u> <optional, depending on tools, links to sub.use cases>

4. You now have the system's functionality captured. When you are ready to work on your estimations, fill in:

<u>Performance Target:</u> <the amount of time this use case should take> OPEN ISSUES SCHEDULE

5. Finally, when you are in the final stages of project estimating, you need to identify all the systems to which you will have to build interfaces. Fill in:

<u>Channel to primary actor:</u> <e.g. interactive, static files, database> <u>Secondary Actors:</u> <list of other systems needed to accomplish use case> <u>Channel to Secondary Actors:</u> <e.g. interactive, static, file, database, timeout>